

CAVALIER

COATED FIRE HOSE



Inside Diameter	Mass per Meter	Short Length Burst Pressure	Recommended Working Pressure	30m Coil Diameter
25mm	0.16 kg	5000 kPa	2000 kPa	0.34 m
38mm	0.22 kg	3500 kPa	1500 kPa	0.39 m
45mm	0.24 kg	3500 kPa	1500 kPa	0.40 m
51mm	0.27 kg	3500 kPa	1500 kPa	0.41 m
65mm	0.40 kg	4500 kPa	1500 kPa	0.42 m
76mm	0.42 kg	4400 kPa	1500 kPa	0.44 m
90mm	0.45 kg	4250 kPa	1500 kPa	0.52 m
102mm	0.52 kg	4000 kPa	1500 kPa	0.54 m

Features

- ✓ Mildew resistant
- ✓ Maintenance free
- ✓ Ready for mounting
- ✓ Can be stored wet
- ✓ High abrasion resistance
- ✓ Many fittings available
- ✓ Working pressure 1500kPa
- ✓ Class M

CAVALIER is a M Class coated fire hose. A close compact weave, combined with a chemical resistant maintenance free, fire hose.

This lightweight, super strength, hose is recommended for industrial and commercial fire protection, general usage in industry, mining, engineering and fire services.

CAVALIER fire hose comes with an exterior coating to further enhance chemical and abrasion resistance. The coating also prevents the hose from being stained by oils and dirt. The standard colour is red. Other colours are available subject to minimum order quantity.

CAVALIER hose is manufactured in Australia to AS2792 Standard.



Global-Mark.com.au®



Crusader Hose Pty Ltd

22 Industry Place Bayswater VIC 3153 Australia
 Telephone: (03) 9720 1100 Facsimile: (03) 9720 5756
 Email: sales@crusaderhose.com.au
 www.crusaderhose.com.au

