

EXCALIBUR

FIRE HOSE



Inside Diameter	Mass per Meter	Short Length Burst Pressure	Recommended Working Pressure	30m Coil Diameter
25mm	0.15 kg	5000 kPa	2000 kPa	0.34 m
38mm	0.22 kg	3500 kPa	1500 kPa	0.39 m
45mm	0.24 kg	3500 kPa	1500 kPa	0.40 m
51mm	0.27 kg	3500 kPa	1500 kPa	0.41 m
65mm	-	-	-	-
76mm	0.45 kg	3500 kPa	1000 kPa	0.48 m
90mm	-	-	-	-
102mm	0.50 kg	2500 kPa	1000 kPa	0.54 m

Features

- ✓ Can be stored wet
- ✓ High burst pressure 3500kPa
- ✓ Working pressure 1500kPa
- ✓ Mildew resistant for long life
- ✓ Many fittings available
- ✓ Low friction loss
- ✓ Versatile
- ✓ Class M

EXCALIBUR is a M Class fire hose popular choice for domestic and commercial fire fighting purposes. It is lightweight very easy to handle and quick to deploy.

EXCALIBUR can be supplied as a ready to go Fire Hose Kit, complete with a shut-off nozzle and fitted couplings. Due to EXCALIBUR'S synthetic construction it is mildew resistant and therefore maintenance free. It can be compactly stored when not in use. EXCALIBUR comes with 12 months warranty.

EXCALIBUR hose is manufactured in Australia to AS2792-1992 Standard.



Crusader Hose Pty Ltd

22 Industry Place Bayswater VIC 3153 Australia
 Telephone: (03) 9720 1100 Facsimile: (03) 9720 5756
 Email: sales@crusaderhose.com.au
 www.crusaderhose.com.au

