

RAPIER

H CLASS FIRE HOSE



Inside Diameter	Mass per Meter	Short Length Burst Pressure	Recommended Working Pressure	30m Coil Diameter
25mm	0.23 kg	5500 kPa	2100 kPa	0.39 m
38mm	0.30 kg	5300 kPa	2100 kPa	0.46 m
45mm	0.36 kg	5250 kPa	2100 kPa	0.47 m
51mm	0.43 kg	5250 kPa	2100 kPa	0.48 m
65mm	0.56 kg	5250 kPa	2100 kPa	0.51 m
76mm	0.80 kg	4500 kPa	1500 kPa	0.53 m
90mm	0.83 kg	4350 kPa	1400 kPa	0.54 m
102mm	0.90 kg	4000 kPa	1000 kPa	0.55 m

Features

- ✓ Reliability
- ✓ High burst pressure 5250kPa
- ✓ Working pressure 2100kPa
- ✓ Mildew resistant for long life
- ✓ Other fittings available
- ✓ Light and quick to deploy
- ✓ Class H
- ✓ Australian Standard AS2792



RAPIER is a popular choice for both fire brigades and industrial plant fire protection. It is high pressure Type 3 fire hose, which is manufactured with an extruded synthetic rubber cover. This extruded cover protects the hose against abrasion and chemical damage.

The interior lining and exterior coating of fire hose jacket is made from high grade PVC nitrile. This extruded cover is highly chemical and abrasion resistant. In addition to the practical protection afforded by the polymer cover, the layflat hose is protected from being stained by oils, grease, chemicals and dirt.

RAPIER is very flexible hose with good handling characteristics. RAPIER is suitable not only for the professional firefighter but also as a strong, high quality layflat for use in plant wash down, mine-dewatering, chemical transfer and as a multi-purpose industrial hose. RAPIER hose comes in standard colour red. Other colours are available subject to minimum order quantity.

RAPIER hose is manufactured in Australia and carries an approval of the Australian Standard AS2792 and the Australian Army DEF 5195A Standard.

Crusader Hose Pty Ltd

22 Industry Place Bayswater VIC 3153 Australia
 Telephone: (03) 9720 1100 Facsimile: (03) 9720 5756
 Email: sales@crusaderhose.com.au
 www.crusaderhose.com.au

