

SUNNYFLO

QUALITY BRAIDED LAYFLAT HOSE



22 Industry Place, Bayswater VIC 3153
 Phone#: (03) 9720 1100 Fax#: (03) 9720 5756
 Email: sales@crusaderhose.com.au
 Website: www.crusaderhose.com.au

This braided layflat hose is ideal for lighter duty applications in Industrial, Irrigation and Mining industries.

SUNNYFLO BLUE

Construction: Braided Polyester Yarns plus PVC cover and inner lining extruded for maximum bonding

Working Temperature: - 21°C to 76 °C



Internal Diameter (mm)	Max. Working Pressure (kPa)	Max. Burst Pressure (kPa)	Wall Thickness (mm)	Standard COIL (m)
38mm	550 kPa	1700 kPa	1.50 mm	100 m
50mm	550 kPa	1700 kPa	1.50 mm	100 m
76mm	550 kPa	1600 kPa	1.60 mm	100 m
102mm	480 kPa	1400 kPa	1.70 mm	100 m
152mm	410 kPa	1350 kPa	1.90 mm	100 m

SUNNYFLO RED

Construction: Thicker Braided Polyester Yarns plus PVC cover and inner lining extruded for maximum bonding

Working Temperature: - 21°C to 76 °C



Internal Diameter (mm)	Max. Working Pressure (kPa)	Max. Burst Pressure (kPa)	Wall Thickness (mm)	Standard COIL (m)
38mm	1000 kPa	3100 kPa	2.00 mm	100 m
50mm	1000 kPa	3100 kPa	2.20 mm	100 m
76mm	1000 kPa	3100 kPa	2.41 mm	100 m
102mm	1000 kPa	3100 kPa	2.59 mm	100 m
152mm	1000 kPa	3100 kPa	3.02 mm	100 m

For heavy duty applications refer to Crusader Hose range.