

Flexiline™ Assembly

Industrial layflat hose assembly

12
MONTH
WARRANTY



Flexiline™ is a flexible layflat hose used for industrial pumping applications. It is robust and typically used for pumping pressures operating up to 15 bar. It can be supplied with a large range of couplings, including Bauer for quick-connect dewatering use. Lengths up to 20 metres can be easily handled. However, for longer lengths we recommend our reel systems; this makes the handling safe, quick and easy.

The polyurethane cover ensures maximum abrasion resistance, and the textile reinforcement gives burst strength. **Flexiline™** is available in 102 mm, 152 mm and 203 mm diameters. All hose is fully tested, and a fitted assembly comes in standard 20 metre lengths. Longer lengths available on request.

IDEAL FOR

- Industrial pumping
- Dewatering hose

FEATURES

- ✓ Tough polyurethane cover
- ✓ Low coil volume for easy handling
- ✓ Securely attached couplings: Bauer, Camlock or Flange
- ✓ Hard-wearing construction use
- ✓ Australian Made

TECHNICAL DATA

Diameter (ID)	102 mm	152 mm	203 mm
	4"	6"	8"
Working pressure	1500 kPa	1500 kPa	1500 kPa
Burst pressure	3000 kPa	3000 kPa	3000 kPa
Tensile load	8 t	14 t	18 t
Weight/m	1.5 kg	2.1 kg	2.8 kg
Avg. single wall thickness	3.2 mm	3.7 mm	4.0 mm
Part #	HNF102XBA	HNF152XBA	HNF203XBA



Scan here to
learn more

Crusader Hose Pty Ltd

22 Industry Place, Bayswater VIC 3153 Australia
e: sales@crusaderhose.com.au p: +61 3 9720 1100

www.crusaderhose.com.au

v.0222

