# **Flexiline**<sup>TM</sup>

## Industrial layflat hose

**12** MONTH



Flexiline™ is a flexible layflat hose used for industrial pumping applications. It is robust and typically used for pumping pressures operating up to 1500 kPa. It can be supplied with a large range of couplings, including Bauer, for quick-connect dewatering use. Lengths up to 20 m can be easily handled. However, for longer lengths, we recommend our reel systems; this makes the handling safe, quick and easy.

The polyurethane cover ensures maximum abrasion resistance and the textile reinforcement gives burst strength. **Flexiline™** is available in 102 mm, 152 mm and 203 mm diameters. All hose is fully tested and a fitted assembly can be supplied with test certification.

### **IDEAL FOR**

- Industrial pumping
- Dewatering hose

#### **FEATURES**

- √ Tough polyurethane cover
- √ Low coil volume for easy handling
- ✓ Suitable with many couplings: Bauer, Camlock & Flange
- √ 12-month warranty
- √ Australian Made

#### **TECHNICAL DATA**

Diameter (ID)	102 mm	152 mm	203 mm
	4"	6"	8"
Working pressure	1500 kPa	1500 kPa	1500 kPa
Burst pressure	3000 kPa	3000 kPa	3000 kPa
Tensile load	8 t	14 t	18 t
Weight/m	1.5 kg	2.1 kg	2.8 kg
Avg. single wall thickness	3.2 mm	3.7 mm	4.0 mm
Part #	HNF102XBA	HNF152XBA	HNF203XBA



Scan here to



22 Industry Place, Bayswater VIC 3153 Australia

e: sales@crusaderhose.com.au p: +61 3 9720 1100







