

Lancer™

Potable water transfer hose



Lancer™ is a potable water transfer hose made exclusively by Crusader Hose. It is designed primarily for municipal use but is also popular in the mining and chemical industries. **Lancer™** is made with a polyester textile reinforcement and extruded with thermoplastic polyurethane (PU). This PU-lined hose is also available in an uncoated version.

Lancer™ is suitable for temporary water bypass when potability is essential. It is also suitable for high-pressure pumping in industrial applications. It is unaffected by UV degradation and is resistant to acids and other chemicals. Its lightweight/low volume coil characteristic makes **Lancer™** easy to handle and store.

Lancer™ is Australian made and manufactured in our ISO 9001 quality-accredited factory. It has Australian Standard AS 4020 approval for drinking water. It also conforms to German BGA DIN39 potability standard. **Lancer™** is backed by a 12-month warranty against manufacturing faults.

IDEAL FOR

- Potable water transfer
- Temporary water bypass
- Mining & chemical industries

FEATURES

- ✓ Potable water approved AS4020
- ✓ Available as extruded or uncoated
- ✓ Working pressure up to 2100 kPa
- ✓ Lightweight and quick to deploy
- ✓ Low storage space
- ✓ Assembly and fittings available
- ✓ Various colours subject to quantity



Scan here to learn more

TECHNICAL DATA: Lancer™ Extruded

Diameter (ID)	19 mm	25 mm	38 mm	51 mm	65 mm	79 mm	90 mm	102 mm
	0.75"	1"	1.5"	2"	2.5"	3"	3.5"	4"
Working pressure	2100 kPa	2100 kPa	2100 kPa	2100 kPa	2100 kPa	1400 kPa	1400 kPa	1000 kPa
Burst pressure	5250 kPa	5250 kPa	5250 kPa	5250 kPa	5250 kPa	3500 kPa	3500 kPa	2500 kPa
Weight/m	0.1 kg	0.2 kg	0.3 kg	0.4 kg	0.6 kg	0.8 kg	0.8 kg	0.9 kg
Part # (blue)	HNL019XUA	HNL025XUA	HNL038XUA	HNL051XUA	HNL065XUA	HNL079XUA	HNL090XUA	HNL102XUA

TECHNICAL DATA: Lancer™ Uncoated

Diameter (ID)	19 mm	25 mm	38 mm	51 mm	65 mm	79 mm	90 mm	102 mm
	0.75"	1"	1.5"	2"	2.5"	3"	3.5"	4"
Working pressure	2100 kPa	2100 kPa	2100 kPa	2100 kPa	2100 kPa	1400 kPa	1400 kPa	1000 kPa
Burst pressure	5250 kPa	5250 kPa	5250 kPa	5250 kPa	5250 kPa	3500 kPa	3500 kPa	2500 kPa
Weight/m	0.11 kg	0.15 kg	0.22 kg	0.27 kg	0.38 kg	0.46 kg	0.50 kg	0.54 kg
Part #	HNL019XAA	HNL025XAA	HNL038XAA	HNL051XAA	HNL065XAA	HNL079XAA	HNL090XAA	HNL102XAA

Crusader Hose Pty Ltd

22 Industry Place, Bayswater VIC 3153 Australia
 e: sales@crusaderhose.com.au p: +61 3 9720 1100

www.crusaderhose.com.au

v.0222

