

Emu™ Clamp

Fitting system for layflat hose



Enjoy the convenience of attaching your couplings on-site.

The **Emu™ Clamp** is a secure fitting method for attaching a coupling to a layflat hose. This non-corrosive aluminium clamp is made up of three segments, that bolt together.

Crusader Hose manufactures Bauer and Flange Table E couplings with the corresponding Emu tail. This ensures the perfect profile for a reliable and safe fitting system.

The **Emu™ Clamp** fitting system has been tested in our laboratory to 2500 kPa. This extreme pressure test is a safeguard, so you can be confident that the coupling won't blow off during pumping.

When considering using the **Emu™ fitting system**, make sure your coupling tails have been specially machined with Emu™ tails. Emu™ Clamps cannot be used with conventional rolled-tailed Bauer or Flanges.

Emu™ Clamp - forged aluminium



Diameter	6"	8"	10"	12"
Working pressure*	2100 kPa	2100 kPa	2100 kPa	2100 kPa
Test pressure	2500 kPa	2500 kPa	2500 kPa	2500 kPa
Torque setting	90 Nm	90 Nm	110 Nm	110 Nm
Weight	2 kg	4 kg	5 kg	5 kg
Part #	CLC152PZA	CLC203PZA	CLC254PZA	CLC305PZA

Bauer Emu™ tail coupling set - galvanised

(set = Bauer male with closure ring & Bauer female with O-ring)



Diameter	6"	8"	10"	12"
Working pressure*	1000 kPa	1000 kPa	1000 kPa	1000 kPa
Test pressure	1500 kPa	1500 kPa	1500 kPa	1500 kPa
Weight/set	11 kg	20 kg	44 kg	46 kg
Part #	CLB152AGT	CLB203AGT	CLB254AGT	CLB305AGT

Flange Table E to Emu™ tail - galvanised



Diameter	6"	8"	10"	12"
Working pressure*	1400 kPa	1400 kPa	1400 kPa	1400 kPa
Test pressure	2000 kPa	2000 kPa	2000 kPa	2000 kPa
Weight/set	4 kg	11 kg	18 kg	19 kg
Part #	CLN152EGT	CLN203EGT	CLN254EGT	CLN305EGT

*Working pressure may vary depending on type of hose & couplings

Crusader Hose Pty Ltd

22 Industry Place, Bayswater VIC 3153 Australia
 e: sales@crusaderhose.com.au p: +61 3 9720 1100

www.crusaderhose.com.au

2212

