

Flexiline™ assembly

Industrial layflat hose assembly

12
MONTH
WARRANTY



Flexiline is a flexible layflat hose used for industrial pumping applications. It is robust and typically used for pumping pressures operating up to 1500 kPa. It can be supplied with a large range of couplings, including Bauer for quick-connect dewatering use. Lengths up to 20 m can be easily handled. However, for longer lengths we recommend our reel systems; this makes the handling safe, quick and easy.

The polyurethane cover ensures maximum abrasion resistance, and the textile reinforcement gives burst strength. **Flexiline** is available in 102 mm, 152 mm and 203 mm diameters. All hose is fully tested, and a fitted assembly comes in standard 20 m lengths. Longer lengths available on request.

IDEAL FOR

- Industrial pumping
- Dewatering hose

FEATURES

- ✓ Tough polyurethane cover
- ✓ Low coil volume for easy handling
- ✓ Securely attached couplings: Bauer, Camlock or Flange
- ✓ Hard-wearing construction use
- ✓ Australian Made

TECHNICAL DATA: Flexiline with Bauer set assembly

Diameter (ID)	102 mm	152 mm	203 mm
	4"	6"	8"
Assembly length	20 m	20 m	20 m
Working pressure	1500 kPa	1500 kPa	1500 kPa
Burst pressure	3000 kPa	3000 kPa	3000 kPa
Tensile load	8 t	14 t	18 t
Weight/m (hose only)	1.5 kg	2.1 kg	2.8 kg
Avg. single wall thickness	3.2 mm	3.7 mm	4.0 mm
Part # Bauer set assembly	CHN102WGP	CHN152WGP	CHN203WGP

NOTE: Flange and Camlock assemblies also available.



Scan here to
learn more

Crusader Hose Pty Ltd

22 Industry Place, Bayswater VIC 3153 Australia
e: sales@crusaderhose.com.au p: +61 3 9720 1100

www.crusaderhose.com.au

2302

