



## Percolating fire hose





**Sabre** is a percolating hose which allows water to seep through the textile reinforcement. By mechanically pin pricking the hose over its length, a thin water layer forms over the hose offering extra protection against burning coals.

**Sabre** is a Class H fire hose with a high working pressure of 2100 kPa. This woven fire hose is made from filament polyester with a synthetic polymer lining and is manufactured with various percolation rates:

- LP Low Percolation (Standard)
- MP Medium Percolation
- HP High Percolation

**Sabre** is fully synthetic, making the fabric imperishable to moisture, unlike the original canvas percolating fire hose. It does not require drying after use, although drying does prevent surface mould stains.



## FEATURES

✓ Percolating fire hose

 $\checkmark$  Easy to handle

- $\checkmark$  No drying required after use
- $\checkmark$  Working pressure 2100 kPa
- 🗸 Australian Made

TECHNICAL DATA

Diameter (ID)	25 mm	38 mm	51 mm	64 mm
	1"	1.5"	2"	2.5"
Working pressure	2100 kPa	2100 kPa	2100 kPa	2100 kPa
Burst pressure	5250 kPa	5250 kPa	5250 kPa	5250 kPa
Weight/m	0.16 kg	0.23 kg	0.28 kg	0.35 kg
30 m coil diameter	0.36 m	0.40 m	0.42 m	0.48 m
Part #	HHS025XLA	HHS038XLA	HHS051XLA	HHS064XLA



Scan here to learn more

## Crusader Hose Pty Ltd

22 Industry Place, Bayswater VIC 3153 Australia e: sales@crusaderhose.com.au p: +61 3 9720 1100 www.crusaderhose.com.au <sup>2404</sup>





